

# 30V & 40V Automotive-Grade N-Channel MOSFET


AEC-Q101 qualified with 175°C junction temperature

PANJIT's latest N-channel power MOSFETs are designed with advanced trench technology to provide excellent figure of merit(FOM), lower  $R_{DS(ON)}$  and capacitance. The new design reduces conduction losses and switching losses while boosting electrical performances. They are available in DFN3333-8L, DFN5060-8L, DFN5060B-8L and TO-252AA packages, which are low profile packages that save spaces. PANJIT offers a comprehensive solution for highly efficient, reliable and space saving PCB layout applications.


## ► Features

- 30V& 40V N-channel advanced trench
- Low  $R_{DS(ON)}$  to minimize conduction losses
- Low FOM to minimize driver losses
- Standard and logic level available
- AEC-Q101 qualified and PPAP capable
- 175°C operating junction temperature


## ► Block Diagrams




## ► Figure of Merit (FOM)



## ► Gate Charge Characteristic



# ➤ Target Applications



- |  |   |   |   |
|--|---|---|---|
| <ul style="list-style-type: none"> <li>• Power motor drive</li> <li>• Oil &amp; water pumps</li> <li>• Infotainment</li> <li>• ADAS</li> <li>• Sensor</li> </ul> | <ul style="list-style-type: none"> <li>• Power supply</li> <li>• LED lighting</li> <li>• DC power tool</li> <li>• Control board</li> <li>• BMS</li> </ul> | <ul style="list-style-type: none"> <li>• Data center</li> <li>• Telecom</li> <li>• Server</li> <li>• Robot</li> <li>• DC Fan</li> </ul> | <ul style="list-style-type: none"> <li>• Wireless charger</li> <li>• Quick charger</li> <li>• Vacuum cleaner</li> <li>• Small appliance</li> <li>• Drone</li> </ul> |
|--|---|---|---|

# ➤ Products

Series	$V_{DS}$ (V)	$V_{GS}$ (V)	$V_{GS(th)}$ Max. (V)	DFN3333-8L	DFN5060-8L	DFN5060B-8L	TO-252AA
30V SGT Logic Level	30	$\pm 20$	2.5	PJQ4534P-AU	PJQ5534-AU		
				PJQ4530P-AU	PJQ5530-AU		
				PJQ4528P-AU	PJQ5528-AU		
				PJQ4526P-AU	PJQ5526-AU		
				PJQ4524P-AU	PJQ5524-AU		
					PJQ5522-AU		
					PJQ5520-AU		
					PJQ5518C-AU*		
				PJQ4548P-AU	PJQ5548-AU	PJQ5948-AU	PJD30N04S-AU
				PJQ4546P-AU	PJQ5546-AU	PJQ5946-AU*	PJD55N04S-AU
40V SGT Logic Level	40	$\pm 20$	2.3		PJQ5544-AU		PJD60N04S-AU
					PJQ5542-AU		PJD65N04S-AU
					PJQ5540-AU		PJD80N04S-AU
					PJQ5540C-AU*		
					PJQ5538S6C-AU*		
					PJQ5536S6C-AU*		
				PJQ4548VP-AU	PJQ5548V-AU	PJQ5948V-AU	PJD25N04V-AU
				PJQ4546VP-AU	PJQ5546V-AU	PJQ5946V-AU*	PJD50N04V-AU
					PJQ5544V-AU		PJD55N04V-AU
					PJQ5542V-AU		PJD60N04V-AU
40V SGT Standard Level	40	$\pm 20$	3.5		PJQ5540V-AU		PJD75N04V-AU
					PJQ5540VC-AU*		
					PJQ5538S6VC-AU*		
					PJQ5536S6VC-AU*		

\* Under development with samples available